DIGITUS® Solar Cable, 20 m, 6 mm², Black, PV Cable, 1500 V DC, UV-Resistant & Weatherproof

DK-SCIC6B-0200

EAN 4016032490746

Solar Installation cable,H1Z2Z2-K,6sqmm,PV 20m,black,solarpanel,inverter,chargecontroller

This high-quality solar cable, with a cross-sectional area of 6 mm² and a length of 20 m, is the ideal connection solution for photovoltaic installations and solar systems. It is ideally suited for use between solar modules, inverters, and other components, thanks to its high voltage resistance of DC 1500 V / AC 1 kV. The tinned copper conductor provides optimal conductivity and excellent corrosion protection. The robust XLPO insulation provides reliable protection against UV radiation, heat, ozone, and moisture. The cable is flexible, abrasion-resistant, and temperature-resistant from -40°C to +90°C. It meets the requirements of the EN 50618:2014 standard and is flame-retardant, ensuring additional safety. With a conductor resistance of ⊠3.39 ⊠/k and an insulation resistance of ⊠500 M⊠·km, it ensures low power losses and high operational reliability. The solar cable is weather-resistant and durable—ideal for long-term outdoor use in professional and residential PV projects.

Safe, efficient, and versatile—this solar cable is the ideal solution for all indoor and outdoor photovoltaic projects.

- Tinned Copper Wire
- Flexible Conductor Assembly (TS 84/0.285 mm)
- Conductor diameter: 3.0 mm
- XLPO Jacket (Outer Shell)
- Insulation diameter: 4.4 mm ±0.1 mm
- Outer diameter: 6.1 mm ±0.2 mm
- Rated voltage: DC 1,500 V / AC 1 kV
- Conductor resistance: ⊠3.39 ⊠/km (at 20°C)
- Insulation resistance: ⊠500 M⊠·km (at 20°C)
- Dielectric strength: AC 6.5 kV / DC 15 kV (5 minutes)
- Spark test: 7 kV
- Operating temperature: -40°C to +90°C
- Flame-retardant in accordance with EN 50618:2014
- Coat color: Black

Package contents

- 20-meter cable loop, black

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	15.90	40.00	20.00	27.00	21,600.00
Packaging Unit Inside	1	1.59	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.59	19.50	19.50	5.50	2,091.38
Net single without Packaging	1	1.55	20.00	20.00	6.00	0.00

Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com