

DIGITUS® CAT 6A Modular Connector, Shielded - 10 pcs.

DN-93905-10

EAN 4016032495086



10x

CAT6A modular coupler, full shielded RJ45 to RJ45, 10 pcs.

Complies with the channel requirements specified in ISO/IEC 11801 for Class EA up to 500 MHz

- 2 x RJ45 jacks
- Assignment: 1:1
- Shielded version
- Housing Material: Brass Sheet - Polished Nickel-Plated
- PCB material: FR4, 1.2 mm thick

- Contact material: Phosphor bronze
- Contact coating: nickel, gold-plated 0.6 μ
- Insertion cycles: $\geq$ 750
- Operating temperature: -10 °C to +50 °C
- Multipack: 10 pieces


Attributes

- Category: CAT 6A

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	5	1.01	23.00	23.00	7.00	3,703.00
Packaging Unit Inside	1	0.20	12.00	12.00	5.00	720.00
Packaging Unit Single	1	0.20	12.00	12.00	5.00	720.00
Net single without Packaging	1	0.10	12.00	12.00	5.00	0.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com