# DIGITUS® Lockable drawer for 482.6 mm (19") network and server cabinets, 1U

**DN-19 KEY-1U**

**EAN 4016032135340**



**1U lockable drawer with handle, 44x483x398 mm grey, for 19" cabinets**

The drawers are suitable for all 482.6 mm 19-inch profile rails in your network or server enclosure. They are also ideal for use in the universal 19-inch equipment racks. For example, they can be used as a lockable document tray or as a keyboard tray. The enclosed mounting brackets for the rear are variable in depth to adapt to the 19" profiles of the cabinet.

**Can be used, for example, as a lockable document holder or keyboard tray.**

- For mounting on the 482.6 mm (19") profile rails
- Height units: 1U
- Product dimensions (HxWxD): 44x483x398 mm
- Available height inside: 31 mm
- Total depth when fully extended: 660 mm
- Installation depth min.-max.: 398-732.5 mm

**Attributes**

- Color: light grey, RAL 7035
- Load capacity: 25 kg
- Units: 1
- Inch form factor (IEC 60297): 482.6 mm (19")

**Package contents**

- 1 x drawer
- 1 x handle
- 1 x key
- Installation set (screws, cage nuts, washers)

**Logistics**

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|---|---|---|---|---|---|---|
| **Packaging Unit Carton** | 5 | 26.43 | 30.00 | 50.00 | 42.50 | 63,750.00 |
| **Packaging Unit Inside** | 1 | 5.29 | 41.50 | 6.00 | 51.00 | 12,699.00 |
| **Packaging Unit Single** | 1 | 5.29 | 41.50 | 6.00 | 51.00 | 12,699.00 |
| **Net single without Packaging** | 1 | 5.08 | 40.00 | 48.10 | 4.40 | 5,244.00 |

**Safety notes**

- When installing and using the accessory product for network cabinets, observe the respective safety instructions of the manufacturer or the cabinet system in which you want to use the accessory.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany


Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

https://www.assmann.com
info@assmann.com