

DIGITUS® CAT 6A Modular Connector, Shielded

DN-93905

EAN 4016032291824



CAT6A modular coupler, full shielded RJ45 to RJ45

Complies with the channel requirements specified in ISO/IEC 11801 for Class EA up to 500 MHz

- 2 x RJ45 jacks
- Assignment: 1:1
- Shielded version
- Housing Material: Brass Sheet Metal - Polished Nickel-Plated

- PCB material: FR4, 1.2 mm thick
- Contact material: Phosphor bronze
- Contact coating: nickel, gold-plated 0.6 µ
- Insertion cycles: ≥ 750
- Operating temperature: -10 °C to +50 °C

Attributes

- Category: CAT 6A

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	10.10	54.50	34.50	13.50	25,383.40
Packaging Unit Inside	50	1.01	25.00	23.00	7.00	4,025.00
Packaging Unit Single	1	0.02	2.00	7.00	12.00	168.00
Net single without Packaging	1	0.01	1.50	2.50	4.00	0.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com